



Certificate number: 2106728

Date issued 9th June 2021

Date expired 8th June 2026 Original/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Manufacturer: Adveco Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

3901770301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Adveco Ltd
Unit 7&8 Armstrong Mall
Southwood Business Park
Farnborough
Hampshire
GU14 0NR



The following products are covered by this certificate -

<p>PRODUCT DESCRIPTION SSB, SSI SST range of stainless steel unvented cylinders provided with an unvented kit supplied with cylinders containing a temperature and pressure reducing valve set at 7.0 bar and an expansion vessel and single check valve (suitable for fluid category 2) . Available as storage tank, indirect or twin coil. ATS3 – Without Production Surveillance.</p>																																																											
<p>MODEL(S)</p> <table border="0"> <thead> <tr> <th>Model</th> <th>Capacity (L)</th> </tr> </thead> <tbody> <tr><td>SSB200</td><td>191;</td></tr> <tr><td>SSB300</td><td>286;</td></tr> <tr><td>SSB500</td><td>481;</td></tr> <tr><td>SSB800</td><td>763;</td></tr> <tr><td>SSB1000</td><td>952;</td></tr> <tr><td>SSB1500</td><td>1426;</td></tr> <tr><td>SSB2000</td><td>2002;</td></tr> <tr><td>SSB2500</td><td>2535;</td></tr> </tbody> </table> <p>No coils; 1 x blanking plate in upper flange; 1x blanking plate in lower flange.</p> <table border="0"> <tbody> <tr><td>SSI200/1.0</td><td>188;</td></tr> <tr><td>SSI300/1.0</td><td>283;</td></tr> <tr><td>SSI500/1.5</td><td>476;</td></tr> <tr><td>SSI800/1.5</td><td>758;</td></tr> <tr><td>SSI800/3.0</td><td>753;</td></tr> <tr><td>SSI1000/5.0</td><td>935;</td></tr> <tr><td>SSI1500/4.0</td><td>1413;</td></tr> <tr><td>SSI1500/6.0</td><td>1407;</td></tr> </tbody> </table> <p>1 x blanking plate in upper flange; 1 x coil in lower flange.</p> <table border="0"> <tbody> <tr><td>SST200/1.0</td><td>184;</td></tr> <tr><td>SST300/1.0</td><td>279;</td></tr> <tr><td>SST500/1.5</td><td>470;</td></tr> <tr><td>SST800/1.5</td><td>752;</td></tr> <tr><td>SST800/3.0</td><td>743;</td></tr> <tr><td>SST1000/5.0</td><td>918;</td></tr> <tr><td>SST1500/4.0</td><td>1399;</td></tr> <tr><td>SST1500/6.0</td><td>1387;</td></tr> <tr><td>SST2000/4.0</td><td>1975;</td></tr> <tr><td>SST2000/6.0</td><td>1963;</td></tr> <tr><td>SST2500/4.0</td><td>2508;</td></tr> <tr><td>SST2500/6.0</td><td>2496;</td></tr> </tbody> </table> <p>1 x coil in upper flange; 1 x coil in lower flange.</p>		Model	Capacity (L)	SSB200	191;	SSB300	286;	SSB500	481;	SSB800	763;	SSB1000	952;	SSB1500	1426;	SSB2000	2002;	SSB2500	2535;	SSI200/1.0	188;	SSI300/1.0	283;	SSI500/1.5	476;	SSI800/1.5	758;	SSI800/3.0	753;	SSI1000/5.0	935;	SSI1500/4.0	1413;	SSI1500/6.0	1407;	SST200/1.0	184;	SST300/1.0	279;	SST500/1.5	470;	SST800/1.5	752;	SST800/3.0	743;	SST1000/5.0	918;	SST1500/4.0	1399;	SST1500/6.0	1387;	SST2000/4.0	1975;	SST2000/6.0	1963;	SST2500/4.0	2508;	SST2500/6.0	2496;
Model	Capacity (L)																																																										
SSB200	191;																																																										
SSB300	286;																																																										
SSB500	481;																																																										
SSB800	763;																																																										
SSB1000	952;																																																										
SSB1500	1426;																																																										
SSB2000	2002;																																																										
SSB2500	2535;																																																										
SSI200/1.0	188;																																																										
SSI300/1.0	283;																																																										
SSI500/1.5	476;																																																										
SSI800/1.5	758;																																																										
SSI800/3.0	753;																																																										
SSI1000/5.0	935;																																																										
SSI1500/4.0	1413;																																																										
SSI1500/6.0	1407;																																																										
SST200/1.0	184;																																																										
SST300/1.0	279;																																																										
SST500/1.5	470;																																																										
SST800/1.5	752;																																																										
SST800/3.0	743;																																																										
SST1000/5.0	918;																																																										
SST1500/4.0	1399;																																																										
SST1500/6.0	1387;																																																										
SST2000/4.0	1975;																																																										
SST2000/6.0	1963;																																																										
SST2500/4.0	2508;																																																										
SST2500/6.0	2496;																																																										
<p>SIZE: See model.</p>																																																											
<p>SCOPE: Manufacturer recommended maximum working pressure of cylinder 6.0 bar, maximum working pressure of coil or coils 12 bar. Maximum operating temperature 95°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. Above ground use only.</p>																																																											
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>																																																											
<p>BACKFLOW PROTECTION NOTES</p>																																																											

UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2106728

N/A.
MARKING Adveco on body. Data label on body with Adveco logo, model no, pressure, temp and other technical information.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements Sealed primary circuits and /or secondary hot water systems shall incorporate a means for accommodating the thermal expansion of water to prevent any discharge from the circuit and/or system except in an emergency situation.

Extra Notes