



LEGEND:

		Inside of jacket	Inside of tubes	
Max. allow. pressure	(PS)	10	-	bar
Min./max. allow. temperature	(TS)	95	-	°C
Test pressure	(PT)	20	-	bar
Capacity	(V)	490	-	L
Surface treatment		pickled and passivated		
Material		1.4571/ 1.4404 316Ti/316 L		
Weight		68		
Tilting tight:		2005 mm		

10	Air vent	Rp 3/4"		DIN 2986			
9	Temperature gauge	Rp 1/2"		DIN 2986			
8	Temperature gauge	Rp 1/2"		DIN 2986			
7	Thermometer	Rp 1/2"		DIN 2986			
6	Drain	Rp 3/4"		DIN 2986			
5	Handhole 120/180	120		RET	O-Ring		
4	Circulation	Rp 1"		DIN 2986			
3	Heating flow	Rp 1 1/2"		DIN 2986			
2	Warm water	Rp 1 1/2"		DIN 2986			
1	Cold water/ heating return	Rp 1 1/2"		DIN 2986			

Nozzle	Denomination	DN	PN	Standard	Facing	Position	Dimension
1	REVISE 10 TO 3/4", TEST PRESSURE					JR	15/02/2021
0	RELEASE					JR	07/01/2021
REV.	CHANGES					BY	DATE CH

REVISE BY COMPUTER ONLY				DO NOT SCALE OFF DRAWING			
-------------------------	--	--	--	--------------------------	--	--	--

ADVECO LIMITED
UNIT 7 & 8, ARMSTRONG MALL
FARNBOROUGH
GU14 0NR
+44(0) 1252 551540
WWW.ADVECO.CO

DIMENSION DRAWING - ATSB500				
DRAWING No: CR203407.r1	DATE: 15/02/2021	REVISION: 1	SCALE: N.T.S.	SIZE: A3