



LEGEND:

		Inside of jacket	Inside of tubes	
Max. allow. pressure	(PS)	10	-	bar
Min./max. allow. temperature	(TS)	95	-	°C
Test pressure	(PT)	20	-	bar
Capacity	(V)	289	-	L
Surface treatment		pickled and passivated		
Material		1.4571/ 1.4404 316Ti/316 L		
Weight		51		
Tilting tight:		1765 mm		

10	Air vent	Rp 3/4"	DIN 2986				
9	Temperature gauge	Rp 1/2"	DIN 2986				
8	Temperature gauge	Rp 1/2"	DIN 2986				
7	Thermometer	Rp 1/2"	DIN 2986				
6	Drain	Rp 3/4"	DIN 2986				
5	Handhole 120/180	120	RET	O-Ring			
4	Circulation	Rp 1"	DIN 2986				
3	Heating flow	Rp 1 1/4"	DIN 2986				
2	Warm water	Rp 1 1/4"	DIN 2986				
1	Cold water/ heating return	Rp 1 1/4"	DIN 2986				

Nozzle	Denomination	DN	PN	Standard	Facing	Position	Dimension
--------	--------------	----	----	----------	--------	----------	-----------


1	REVISE 10 TO 3/4", TEST PRESSURE	JR	15/02/2021	
0	RELEASE	JR	07/01/2021	
REV.	CHANGES	BY	DATE	CH

REVISE BY COMPUTER ONLY	DO NOT SCALE OFF DRAWING
-------------------------	--------------------------



ADVECO LIMITED  
UNIT 7 & 8, ARMSTRONG MALL  
FARNBOROUGH  
GU14 0NR  
+44(0) 1252 551540  
WWW.ADVECO.CO

DIMENSION DRAWING - ATSB300

DRAWING No: CR203404.r1	DATE: 15/02/2021	REVISION: 1	SCALE: N.T.S.	SIZE: A3
----------------------------	---------------------	----------------	------------------	-------------