



LEGEND:

		Inside of jacket	Inside of tubes	
Max. allow. pressure	(PS)	10	20	bar
Min./max. allow. temperature	(TS)	95	200	°C
Test pressure	(PT)	20	32	bar
Capacity	(V)	212	9	L
Surface treatment		pickled and passivated		
Material		1.4571/ 1.4404 316Ti/ 316L		
Weight		79		kg
Tilting height:		1395 mm		

11	Air vent	Rp 1"		DIN 2986			
10	Thermometer	Rp 1/2"		DIN 2986			
9	Thermometer	Rp 1/2"		DIN 2986			
8	Handhole 120/180	120	RET	O-Ring			
7	Temperature gauge	Rp 1/2"		DIN 2986			
6	Temperature gauge	Rp 1/2"		DIN 2986			
5	Warm water	Rp 1"		DIN 2986			
4	Circulation	Rp 3/4"		DIN 2986			
3	Heating flow	R 1"		DIN 2982			
2	Heating return	R 1"		DIN 2982			
1	Cold water	Rp 1"		DIN 2986			
Nozzle	Denomination	DN	PN	Standard	Facing	Position	Dimension

1	REVISE 11 TO 1", TEST PRESSURE 20 BAR	JR	15/012/2021	
0	RELEASE	JR	08/01/2021	
REV.	CHANGES	BY	DATE	CH

REVISE BY COMPUTER ONLY

DO NOT SCALE OFF DRAWING

ADVECO LIMITED
UNIT 7 & 8, ARMSTRONG MALL
FARNBOROUGH
GU14 0NR
+44(0) 1252 551540
WWW.ADVECO.CO

DIMENSION DRAWING - ATSH200

DRAWING No: CR203702.r1	DATE: 15/02/2021	REVISION: 1	SCALE: N.T.S.	SIZE: A3
----------------------------	---------------------	----------------	------------------	-------------