



LEGEND:

		Inside of jacket	Inside of tubes	
Max. allow. pressure	(PS)	10	10	bar
Min./max. allow. temperature	(TS)	95	110	°C
Test pressure	(PT)	20	20	bar
Capacity	(V)	756	39 / 18	L
Surface treatment		pickled and passivated		
Material		1.4571/ 1.4404 316Ti/ 316L		
Weight		175		kg
Tilting height:		2050		mm

9	Air vent	Rp 1"		DIN 2986			
8.2	Solar heating return	R 1 1/4"		DIN 2982			
8.1	Solar heating flow	R 1 1/4"		DIN 2982			
7	Circulation	Rp 3/4"		DIN 2986			
6.2	Heat pump heating return	R 1 1/2"		DIN 2982			
6.1	Heat pump heating flow	R 1 1/2"		DIN 2982			
5	Thermometer	Rp 1/2"		DIN 2986			
4.1...4.3	Temperature gauge	Rp 1/2"		DIN 2986			
3	Handhole Ø120/180	120		RET			
2	Warm water	Rp 1 1/2"		DIN 2986			
1	Cold water	Rp 1 1/2"		DIN 2986			
Nozzle	Denomination	DN	PN	Standard	Facing	Position	Dimension

1	REVISE TEST PRESSURE 20 BAR		JR	15/02/2021	
0	RELEASE		JR	11/01/2021	
REV.	CHANGES		BY	DATE	CH

REVISE BY COMPUTER ONLY	DO NOT SCALE OFF DRAWING
-------------------------	--------------------------



ADVECO LIMITED
UNIT 7 & 8, ARMSTRONG MALL
FARNBOROUGH
GU14 0NR
+44(0) 1252 551540
WWW.ADVECO.CO

DIMENSION DRAWING - ATSR750				
DRAWING No: CR203804.r1	DATE: 15/02/2021	REVISION: 1	SCALE: N.T.S.	SIZE: A3